

IP KVM-1500CB Series

8ports/16ports 1U rack mount 15" LED KVM drawer over IP



Main features

- « KVM (keyboard, video ,mouse) access over IP and analogous telephone line (modem needed) .
- « Full control under any OS, in BIOS mode , during boot, at Blue Screen
- « 256 bit SSL encryption of all transmitted data and certificate management
- « Port to connect a user console for direct analogous access to KVM switch
- « Can be used with most standard KVM
- « To switch the host computer though the hotkey or OSD menu, which can manage up to 512 computers.
- « Password security protection, only authorized users can view and manage on-line computer.
- « Support a variety of brand industrial computer and the server:

EVOC/Lenovo/IBM/DELL/HP/SUN, etc

« Support various operating system: Microsoft, Linux, Unix, etc.

Introduction

« IP-KVM switch can save your Money ,Time, Space, Equipment and Power . IP KVM switch defines a new class of remote KVM switch devices. IP KVM switch combines digital remote KVM access via IP networks with comprehensive and integrated system management.

« IP KVM Switch provides convenient, remote KVM access and control via LAN or internet . it captures, digitizes, and compresses video signal and transmits it with keyboard and mouse signals to and from a remote computer. IP KVM switch provides a non-intrusive solution for remote access and control . Remote access and control software runs on its embedded processors only but not on mission-critical servers, so that there is no interference with server operation or impact on network performance.

Specification

Model	IP KVM-1508CB	IP KVM-1516CB
Computer connect	Direct : 8	Direct : 16
	Max : 256	Max : 512
Connector port	8 /16 * HDB-15 female (Yellow)	
IP Module console	1* RJ45 port , 1* VGA port (male) , 1* USB	
Selection connection	Support daisy-chained serial connection(8 levels) and stacking cascade connection (2 levels).	
Keyboard	104 Mechanical mute Keyboard	
Mouse	Touchpad	
Switch Mode	Hotkey , OSD Menu	
Auto scanning interval	5 - 99 second	
Power input	DC12V input , (AC100-240V 47-63Hz, 35W) optional	
LED Indicator	Power indicator	2
	Selection indicator	16
	Boost on-line indicator	16
	Num Lock	1
	Caps Lock	1
	Scroll Lock	1
	Operating Temp	-10℃~60℃

Work environment	Storage Temp	-20℃~70℃
	Humidity	0%-95%RH
Cabinet Material	high-strength and Anti-corrosive steel plate	
Color	Insulated black (optional)	
For Cabinet	800-1040mm	
Net weight	12KG-16KG	
Gross Weight	16KG-20KG	
Dimension	520mm*480.4mm*44mm (L x W x H)	
Package	708mm*608mm*195mm (L x W x H)	
Certificate	CE , FCC , RHOS	

Ordering information

IPKVM-1508CB	1U Rack mount 15" TFT LED KVM switch, W/ Keyboard +touchpad ,W/ 8 VGA port over IP access, W/ 12V power supply
IPKVM-1516CB	1U Rack mount 15" TFT LED KVM switch , W/ Keyboard +touchpad , W/ 16 VGA port over IP access, W/ 12V power supply

IO View





Technical drawing of the K 1000 cabinet showing three views: front, side, and top.

- Front View:** Shows a cabinet with a width of 440 mm and a height of 480,4 mm. It features a handle on the left side and two drawers at the bottom.
- Side View:** Shows the depth of the cabinet, which is 440,4 mm.
- Top View:** Shows the width of the cabinet, which is 520 mm.